

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION					
NFPA Rating: Health-; Flammability-; Reactivity-; Special-;			HMIS Rating: Health-1; Flammability-0; Reactivity-0; Protection-N/A		
Manufactured For: Triple S Address: 2 Executive Drive Billerica, MA 01821			DOT Hazard Classification: None Identity: (Trade Name On Label) SSS Dumpster Fresh		
Date Prepared: JANUARY 1, 2001 For Information: 800-323-2251			Prepared By: In Case of Emergency: 888-779-1339		
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL & COMMON NAMES (Hazardous Components >1%; Carcinogens >0.1%)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source
Fuller's Earth	8031-18-3*		5 mg/m ³	10 mg/m ³	
Contains Crystalline Silica - 0-5%					
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point:	N/A	Specific Gravity (H₂O=1):		2.2	
Vapor Pressure: PSIG @ 70 degrees F:	N/A	Vapor Pressure (mm Hg & Temperature):		N/A	
Vapor Density: (Air=1)	N/A	Evaporative Rate:		None	
Solubility in Water:	Negligible	Water Reactive:		None	
Appearance & Odor: Gray/Tan granules with a heavy cherry odor					
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA					
Flammability per USA Flame		Auto Ignition Temperature		Flammability Limits in Air by Volume %:	
Projection Test (aerosols): N/A		N/A		% LEL: None % UEL: None	
FLASH POINT & METHOD USED: (non-aerosols): None			SPECIAL FIRE FIGHTING PROCEDURES: None		
EXTINGUISHER MEDIA: Non-Flammable					
Unusual Fire & Explosion Hazards:					
SECTION 4 - REACTIVITY HAZARD DATA					
STABILITY <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE			HAZARDOUS POLYMERIZATION <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR		
Incompatibility (Mat. To Avoid): Hydrofluoric Acid			Conditions to Avoid: None Known		
Hazardous Decomposition Products: None Known					
SECTION 5 - HEALTH HAZARD DATA					
PRIMARY ROUTES OF ENTRY: <input checked="" type="checkbox"/> INHALATION <input type="checkbox"/> INGESTION <input type="checkbox"/> SKIN <input type="checkbox"/> EYE <input type="checkbox"/> NOT HAZARDOUS					
ACUTE EFFECTS: Inhalation of sufficient quantities of respirable crystalline silica dust can produce progressive symptoms					
Inhalation: Cough, labored breathing, breathing discomfort, wheezing.					
Eye contact: Irritation may occur.			Skin Contact: Irritation may occur.		
Ingestion:					
CHRONIC EFFECTS: Repeated or prolonged exposure to respirable crystalline silica may cause chronic lung injury (silicosis).					
Medical Conditions Generally Aggravated by Exposure: Lung fibrosis may create lung enlargement, heart/pulmonary failure; smoking aggravates the effects.					
EMERGENCY FIRST AID PROCEDURES					
Eye Contact: Wash with water. If irritation persists, see physician.					
Skin Contact: Wash with water. If irritation persists, see physician.					
Inhalation: Remove person to fresh air, give artificial respiration as needed, seek medical attention if needed.					
Ingestion: Clear material from mouth. If large amount is ingested, see physician.					
SECTION 6 - CONTROL AND PROTECTIVE MEASURES					
Respiratory Protection (specify type): MSHA or NIOSH approved respirators with HEPA filters if exposure level exceeds PEL.					
Protective Gloves: Optional			Eye Protection: Optional		
Ventilation Requirements: Ventilation must be sufficient to reduce the level of respirable crystalline silica = to or < PEL.					
Other Protective Clothing & Equipment: Optional					
Hygienic Work Practice: Use good housekeeping practices. Follow precautions listed above.					
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING & USE					
Steps To Be Taken If Material Is Spilled/Released: Vacuum or wet sweep; use adequate ventilation, use of respirator advisable.					
Waste Disposal Methods: Transfer sweeping to sealable containers. Do not flush down drain. Dispose in accordance with Federal, State & Local regulations.					
Precautions To Be Taken In Handling & Storage: Store in a dry area away from sharp objects which can tear or puncture containers.					
Other Precautions &/Or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Spent clay mixed with oil may be combustible in air. Use nitrogen or steam as filter press purge. Air is not recommended. Cover spent clay with water prior to disposal.					

THE INFORMATION AND RECOMMENDATIONS IN THIS DATA SHEET ARE BELIEVED TO BE CORRECT AND RELIABLE. HOWEVER, THE DATA IS OFFERED FOR CONSIDERATION AND VERIFICATION BY THE USER AND TRIPLE S OFFERS NO GUARANTEE, WARRANTY OR REPRESENTATION AS TO THE ACCURACY OR COMPLETENESS OF THE DATA.