

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION						
NFPA Rating: Health-2; Flammability-2; Reactivity-0; Special--			HMIS Rating: Health-2; Flammability-2; Reactivity-0; Personal Protection-B			
Manufactured For: Triple S Address: 2 Executive Park Dr. Address: Billerica, MA 01862			DOT Hazard Classification: ORM-D Identity (trade name as used on label): SSS Metal Cleaner & Polish #05013			
Phone: 978-667-7900			MSDS Number: A00141 Revision- 16			
Emergency Medical Information: 1-888-779-1339			Date Prepared: 08/20/08 Prepared By: LF/IB			
NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
PETROLEUM DISTILLATE		64742-52-5	No	5mg/M3	5mg/M3	d
PETROLEUM DISTILLATE		64742-47-8	No	100	100	d
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d
		74-98-6	No	1000	1000	d
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: N/A			Specific Gravity (H2O=1): Concentrate Only = .856			
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60			Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A			
Vapor Density (Air = 1): N/E			Evaporation Rate (= 1): N/E			
Solubility in Water: Insoluble			Water Reactive: No			
Appearance and Odor: Clear liquid, lemon fragrance.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) FLAMMABLE >18 Inches		Auto Ignition Temperature N/E		Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E		
FLASH POINT AND METHOD USED (non-aerosols): N/A			EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.			
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY [X] STABLE [] UNSTABLE			HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR			
Incompatibility (Mat. to avoid): Strong oxidizers.			Conditions to Avoid: Open flame, welding arcs, heat, sparks.			
Hazardous Decomposition Products: CO, CO2.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [X] EYE [] NOT HAZARDOUS						
ACUTE EFFECTS						
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.						
Eye Contact: Mild irritation.			Skin Contact: Mild irritation due to defatting of the skin.			
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, lung and kidney damage.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH for organic vapor.						
Protective Gloves: Polyethylene gloves			Eye Protection: Safety glasses recommended.			
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.						
Other Protective Clothing & Equipment: Eyewash station if desired.						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH TO SEWER.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only