MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION

NFPA Rating: Health-1; Flammability-1; Reactivity-0; Special-	**HMIS Rating:** Health-1; Flammability-1; Reactivity-0; Personal Protection-B
Manufactured For: Triple S Address: 2 executive Park Dr. Billerica, MA 01862	**DOT Hazard Classification:** ORM-D **Identity** (trade name as used on label)**:** **SSS Multi-Surface Cleaner & Polish**
Phone: 978-667-7900	**MSDS Number:** A00145 Revision- 2
EMERGENCY RESPONSE NUMBER: 1-800-255-3924 NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA	Information Calls: (978)667-7900 Date Prepared: 10/02/00 Prepared By: CH

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d
MINERAL OIL	8042-47-5	No	5mg/m3	5mg/m3	d

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A	**Specific Gravity** (H2O=1): Concentrate Only = .963
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60	**Vapor Pressure** (Non-Aerosols)(mm Hg and Temperature): N/A
Vapor Density (Air = 1): N/E	**Evaporation Rate** (BuAc = 1): N/E
Solubility in Water: Soluble	**Water Reactive:** No

Appearance and Odor: Yellowish foam with fresh fragrance.

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY as per CPSC/USA FLAME PROJECTION TEST (aerosols) **NOT-FLAMMABLE**	Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E

FLASH POINT AND METHOD USED (non-aerosols): N/A **SPECIAL FIRE FIGHTING PROCEDURES:** Self-contained breathing apparatus.	**EXTINGUISHER MEDIA:** Foam, dry chemical, carbon dioxide, water.

Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY [X] STABLE [ ] UNSTABLE	**HAZARDOUS POLYMERIZATION** [ ] WILL [X] WILL NOT OCCUR
Incompatibility (Mat. to avoid): Strong oxidizers.	**Conditions to Avoid:** Open flame, welding arcs, heat.

Hazardous Decomposition Products: CO, CO2.

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: [X] INHALATION [ ] INGESTION [X] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS

ACUTE EFFECTS:

Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.

Eye Contact: Mild irritation.	**Skin Contact:** May aggravate existing skin conditions.

Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.

CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause headaches, dizziness and nausea.

Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush with water for at least 15 minutes. If irritated, seek medical attention.

Skin Contact: Wash with soap and water. If irritated, seek medical attention.

Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.

Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH in a positive pressure mode.

Protective Gloves: Latex if skin easily irritated.	**Eye Protection:** Safety glasses recommended.

Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.

Other Protective Clothing & Equipment: None

Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken If Material Is Spilled Or Released: Absorb spilled liquid with suitable medium. Place in closed drum for proper disposal. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH LIQUID TO SEWER.

Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.

Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.

Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only