

# Material Safety Data Sheet

Product Number: 08128, 08129, 08133, 08134, 08135, 08136, 08137, 08138, 08139 Product Name: Metered Dry Air Fresheners (All Fragrances)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

## Section I – Product and Company Information

Manufactured for: Triple S	Emergency Telephone Number: (888) 779-1339
Address: 2 Executive Park Drive Billerica, MA 01862	Telephone Number for Information: (800) 323-2251
	Date Prepared: 05-27-2010
	Signature of Preparer (optional)

HMIS Ratings      Health: 2      Flammability: 4      Reactivity: 1      Personal Protection: A

## Section II - Hazardous Ingredients/Identity Information

Hazardous Components	CAS #	OSHA PEL	ACGIH TLV	Other Limits % (optional)
Acetone	CAS # 67-64-1	750 ppm	750 ppm	N/A
Liquefied Petroleum Gas	CAS # 68476-86-8	1000 ppm	800 ppm	N/A
Fragrance	No CAS #	N/A	N/A	N/A

## Section III - Physical/Chemical Characteristics

Boiling Point	N/D	Specific Gravity (H <sub>2</sub> O = 1)	0.70 – 0.80
Vapor Pressure (mm Hg.)	N/D	Melting Point	N/A
Vapor Density (AIR = 1)	>1	Evaporation Rate	<1

Solubility in Water: N/E

Appearance and Odor: Fine mist spray with various fragrances.

## Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) -156°F TCC	Flammable Limits	LEL 0.6%	UE 19%
--------------------------------------	------------------	-------------	-----------

Extinguishing Media: Foam, dry chemical, water, or carbon dioxide (CO<sub>2</sub>)

Special Fire Fighting Procedures: Water may be used to cool closed containers to prevent pressure buildup and possible auto ignition or explosion when exposed to extreme heat. Wear a full face positive pressure self contained breathing apparatus when fighting fires.

Unusual Fire and Explosion Hazards: CAUTION: Contents under pressure. Exposure to temperatures above 120°F may cause bursting.

<b>Section V - Reactivity Data</b>			
Stability	Unstable		Conditions to Avoid: Avoid open flames and temperatures > 120F
	Stable	X	
Incompatibility (Materials to Avoid): Avoid contact with strong oxidizing agents and strong acids.			
Hazardous Decomposition or Byproducts: Combustion may produce carbon monoxide.			
Hazardous Polymerization	May Occur		Conditions to Avoid: N/A
	Will Not Occur	X	
<b>Section VI - Health Hazard Data</b>			
Route(s) of Entry: Inhalation: Yes                      Skin: Yes                      Ingestion: Yes			
Health Hazards (Acute and Chronic): Acute – High vapor concentrations can cause irritation of the eyes and respiratory system. Chronic – Skin irritation can occur among sensitive individuals following repeated contact.			
Carcinogenicity: NTP: No                      IARC Monographs: No                      OSHA Regulated: No			
Signs and Symptoms of Exposure: INHALATION - Shortness of breath, dizziness and light headedness. EYES – Irritation and redness. SKIN – Irritation. INGESTION - May cause chemical pneumonia if aspired into lungs.			
Medical Conditions Generally Aggravated by Exposure: None Known			
Emergency and First Aid Procedures: INHALATION: Move to fresh air. SKIN: Wash with plenty of soap and water and seek medical attention if irritation persists. INGESTION: Seek medical attention or call your nearest poison control center.			
<b>Section VII - Precautions for Safe Handling and Use</b>			
Steps to be Taken in Case Material is Released or Spilled: If container is ruptured and begins to leak, place in a well ventilated area. Eliminate all ignition sources. Wash spills with soap and water. For large spills soak up with inert absorbent material such as sand.			
Waste Disposal Method: Landfill for absorbent material. Do not incinerate. Dispose of in accordance with local, state and federal regulations.			
Precautions to be Taken in Handling and Storing: Do not store near heat or open flame or temperatures exceeding 120°F.			
Other precautions: Handle as a flammable liquid			
<b>Section VIII - Control Measures</b>			
Respiratory Protection (Specify Type): None required			
Ventilation	Local Exhaust	Adequate	Special: N/A
	Mechanical (General)	Adequate	Other: N/A
Protective Gloves: Rubber or plastic for prolonged contact	Eye Protection: Safety goggles for splash protection		
Other Protective Clothing or Equipment: Eye wash/shower facility nearby			
Work/Hygienic Practices: Good housekeeping practices. Avoid skin/eye contact.			