



MIRAQUEST PLUS

ULTRA HIGH SPEED FLOOR FINISH

SELLADOR/ACABADO

Technical Data

Areas of Use

Designed to be used as part of an ultra high speed floor maintenance system in:

- Hospitals, nursing homes, doctors offices
- Schools, universities, child care centers
- Supermarkets, malls, retail stores

Specifications

Available Sizes	4/1G, 5G, 55G
Physical State	Liquid
Color	Milky White
Fragrance	Acrylic
Total solids	21%
Metal Interlocked	Yes
Initial Gloss	Very High
Leveling	Excellent
Scuff Resistance	High
Burnisher Response	Outstanding
Specific Gravity	1.029
pH	9.0

HMIS Hazard Rating

Health	1
Flammability	0
Reactivity	0
Personal Protection	A

What the Pros Know

Don't apply if floor surface temperature is less than 45°F. Powdering will result. Allow extra curing time in humid conditions. Rushing coats will cause recoat disturbance and dulling. Don't overwork finish - just spread evenly and allow to dry. Apply finish only with a clean finish mop - never use a cleaning mop. See label for complete directions and use only as directed.

MIRAQUEST PLUS exceeds the minimum slip resistance requirements for floor finishes when tested in accordance with ASTM 2047-82 (UL test procedure).


- High solids - Requires fewer coats
- Latest polymer technology - Durable wet look gloss
- Designed for high traffic - Unequaled gloss and scuff resistance
- Unique polymer system - Easy to apply, repair, and re-coat
- Tough film - Compatible with UHS electric, battery, and propane equipment
- Removes with emulsifying strippers - Easy to remove

The latest floor care polymer technology is used to create a product that delivers wet-look gloss and outstanding durability. The unique polymer system provides ease of use and even application onto resilient flooring or most non-resilient surfaces. The finish resists scuffs, abrasions, black heel marks and offers outstanding chemical resistance. The ideal foundation for an UHS floor maintenance system.

Following a planned maintenance schedule will prolong the life of your finish. Extending the life of your finish extends the time between required "scrub & recoats" and "strip-outs", resulting in a reduction of overall labor cost.

Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



Thoroughly strip or clean floor and allow to dry prior to application. Stripping all old coatings is recommended prior to initial application.



Apply this product in a uniform, medium coat. Allow each coat to dry to the touch prior to applying additional coats. Three to five coats are recommended for initial application (2 to 3 coats when used over a seal).



Restore gloss by applying Meteor UHS Restorer or occasional dry burnishing (use 1500+ RPM equipment). Consult your Triple S representative for proper pad selection.

Designed for
UHS systems

Latest polymer
technology

Premium quality

