

PRO SERIES

PIT STOP

HEAVY DUTY FLOOR STRIPPER
SOLE DESMOLDADOR



Technical Data

Areas of Use

- Vinyl Tile
- Terrazzo
- Ceramic Tile
- Flagstone

Specifications

SSS Item Numbers	48076
Available Sizes	2.5G
Color	Light amber
Active Ingredients	14.0 ± 0.5%
Fragrance	Sassafras
pH	12.2 - 12.7
Viscosity	Slightly viscous
Foam	Low
Abrasives	None
Solubility	Complete with water
Emulsification	Excellent
Detergency	Excellent
Rinsability	Excellent
Flash Point	None (waterbased)
Biodegradability	Complete
Storage/Stability	2 years
Weight Per Gallon	8.68 lbs./gal.
Freeze/Thaw Stability	Keep from freezing

HMIS Hazardous Materials I.D. System

Health	2
Flammability	0
Reactivity	0
Personal Protection	B

What the Pros Know

Limit stripping area to a size that can be stripped and wet vacuumed before evaporation starts. Flooding too large an area may require another application of stripper, rescrubbing and require more time.

Description

A heavy duty, non-ammoniated stripper that quickly unlocks all water-based waxes, finishes, and sealers. It is highly concentrated and very effective. Contains no harsh solvents or abrasives.

Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



Dilute PIT STOP from 1:3 to 1:14 (32 oz. to 9 oz./gal) with cold or warm water, depending on age and build-up of finish.



1. After sweeping the floor clean, apply at a rate of 50-300 square feet per gallon. Apply liberally to ensure complete wetting. Be sure to completely cover floor to baseboards.
2. Allow to stand for 3 to 5 minutes, DO NOT ALLOW TO DRY.
3. Scrub the wet floor with a floor machine using a stripping pad to break the softened film scrub.
4. Pick-up solution using a mop, wet vac or automatic scrubber. If mop is used for pick-up, use extreme care to remove all residue and change water frequently.
5. Damp mop thoroughly with clean, cool water to remove all residues, and allow to dry before applying finish.

*Designed for
Mechanical
Stripping*

Non-Ammoniated

*Contains No
Harsh
Solvents*



MATERIAL SAFETY DATA SHEET

N/A=Not Applicable

Prepared by: Regulatory Affairs Dept.

(Prepared According to 29 CFR 1910.1200)

Effective Date: 1/09 Revision: n/a

SECTION 1-PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Product Name: Pit Stop
Generic Name: Non-ammoniated, Heavy Duty Floor Stripper
Chemical Family: N/A
Formula: N/A
Triple S Product No.: 48076

Manufactured For: Triple S
Address: 2 Executive Park Drive Billerica, MA 01862
Phone #: 800-323-2251

SECTION 2-INGREDIENT INFORMATION

CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Water	7732-18-5	to 100			
Monoethanolamine	141-43-5	5 to 10	3 ppm	3 ppm	6 ppm
Potassium Tall Oil Soap	61790-44-1	0 to 5			
Nonionic Surfactant	9016-45-9	0 to 5			
Sodium Silicate	1344-09-8	0 to 5			
Tetrasodium Pyrophosphate	7722-88-5	0 to 5			
Tetrasodium EDTA	64-02-8	0 to 5			
Perfume Oils	N/A	0 to 5			

SECTION 3-PHYSICAL DATA

Boiling Point (°F): 212 F.
Vapor Pressure: 20mm Hg @ 68 F.
% Volatile: 85+
Solubility in Water: Complete
Physical Description: Thin light amber liquid with characteristic odor.

Specific Gravity: 1.042
Vapor Density (Air=1): >1
pH: 12.2-12.7
Evaporation Rate (Water=1): <1

SECTION 4-FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/A
Upper Explosion Limit: N/A
Extinguishing Media: N/A
Special Firefighting Procedures: Non Flammable
Unusual Fire and Explosion Hazards: N/A

SECTION 5-REACTIVITY DATA

Stability: Stable
Hazards Decomposition Products: Alkaline vapors in a fire.

Hazardous Polymerization: None
Incompatibility (Materials to Avoid): Strong acids.

SECTION 6-STORAGE AND HANDLING INFORMATION

Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only. Avoid contact with eyes, skin and clothing. Wear protective eyewear and footwear when handling. Avoid breathing of vapors. Use in well-ventilated area.

SECTION 7-HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:
Skin: Skin irritant. May cause moderate reddening, and swelling.
Eyes: Eye irritant. Liquid and mists may damage eyes, causing corneal damage.
Inhalation: Mists may be irritating to mucous membranes in the nose, throat, and lungs.
Ingestion: Irritating and corrosive to the mouth and throat. May cause headache, nausea, abdominal pain, vomiting, and diarrhea. Excessive amounts may cause collapse.
First Aid Procedures:
Skin: Flush with water. Seek medical attention if irritation persists. Avoid contact with eyes, skin, and clothing.
Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention if irritation persists.
Inhalation: Get to fresh air. Seek medical attention if irritation persists.
Ingestion: Do not induce vomiting. Drink large quantities of water. Seek medical attention immediately.

SECTION 8-SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use in well-ventilated area.
Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit.
Protective Gloves: Chemical resistant rubber or neoprene.
Eye Protection: Safety glasses or chemical splash goggles.
Other Protective Equipment: Protective footwear e.g. rubber boots should be worn when using product. Eyewash should be available nearby.

SECTION 9-SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.
Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. Consult local authorities for disposal in public sewer. Do not dispose of into storm drain, stream, river or to ground. Rinse container thoroughly before discarding in trash.

SECTION 10-REGULATORY INFORMATION

SARA Title III - Section 311/312 -Hazard Categories:
 No - Fire Hazard
 No - Sudden Release of Pressure Hazard
 No - Reactivity Hazard
 Yes - Immediate (acute) Health Hazard
 No - Delayed (chronic) Health Hazard

Shipping Information:
 FOR CONTAINERS > 1 Gallon : Cleaning Compound
 FOR 1 GALLON CONTAINERS : Cleaning Compound
 FOR CONTAINERS < 1 GALLON : Cleaning Compound

HMIS Hazardous Materials Identification System

Health	2
Flammability	0
Reactivity	0
Personal Protection	B

FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: ER# 1-888-779-1339

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS#	Chemical Name	Percent by Weight
	None	

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.

CAS#	Chemical Name	Percent by Weight
	None	

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product