

PRO SERIES

VICTORY LANE

ULTRA HIGH SOLIDS LOW MAINTENANCE FINISH

FINAL BAJO DEL MANTENIMIENTO DE LOS SÓLIDOS ULTRA ALTOS



Technical Data

Areas of Use

- Health care
- Schools
- Retail Buildings
- Offices
- Any facility using a low maintenance program

Specifications

SSS Item Numbers	48083
Available Sizes	2.5G
Color	Milky White
Fragrance	Mild
Type	Highly Crosslinked Acrylic
Non-volatile Solids	24.0±0.5%
pH	8.0 - 9.0
Dry/Recoat Time	1 hour min.
Slip Resistance	0.5 min. by ASTM D2047
Gloss	95+ specular
Leveling	Excellent
Buffability	Spray Buff or Restorer
Removability	With instant type strippers
Detergent Resistance	Excellent
Waterspot Resistance	Excellent
Heel Mark Resistance	Excellent
VOC Content	0.361 lbs./gal.
Viscosity	Water thin
Storage/Stability	2 years
Freeze/Thaw Stability	Keep from freezing
Weight Per Gallon	8.65 lbs./gal.
Coverage	1800-2200 sq. ft./gal.

HMIS Hazardous Materials I.D. System

Health	1
Flammability	0
Reactivity	0
Personal Protection	A

What the Pros Know

Don't apply if floor surface temperature is less than 45° F. Powdering will result. Allow extra curing time in humid conditions. Rushing coats will cause recoat disturbance and dulling. Don't overwork finish - just spread evenly and allow to dry. Apply finish only with a clean finish mop - never use a cleaning mop. See label for complete directions and use only as directed.

Description

An ultra high solids low maintenance floor finish with exceptional durability and buffability. When used on high traffic floors, wear levels are dramatically superior to conventional floor finishes on the market today. This high gloss product is ready for traffic immediately after application without burnishing. After weeks of wear it will snap back to its original shine with the aid of a spray buffing with a 175-300 rpm machine.

Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



PREPARATION: If stripping is necessary, use a high quality stripper and follow directions accordingly. If floor is in good condition and stripping is not necessary; sweep up excess dirt and dust and then clean with a good quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow to dry completely.

FINISHING: Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Two or three coats are desired initially, depending on the condition of the floor and gloss desired.

MAINTENANCE: The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

High Solids

Ultra Durable

Low Maintenance



MATERIAL SAFETY DATA SHEET

N/A=Not Applicable

Prepared by: Regulatory Affairs Dept.

(Prepared According to 29 CFR 1910.1200)

Effective Date:1/09 Revision: n/a

SECTION 1-PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Product Name: Victory Lane
Generic Name: Ultra High Solids Low Maintenance Finish
Chemical Family: Acrylic Wax Blend
Formula: Proprietary
Triple S Product Number: 48083

Manufactured For: Triple S
Address: 2 Executive Park Drive Billerica, MA 01862
Phone #: 800-323-2251

SECTION 2-INGREDIENT INFORMATION

CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Water	7732-18-5	to 100			
Acrylic Copolymer Dispersion	63744-68-3	45 to 50			
Resin Solution	65405-63-2	5 to 10			
Polypropylene Wax	25722-45-6	0 to 5			
Polyethylene Wax	68441-17-8	5 to 10			
Tributoxy Ethyl Phosphate	78-51-3	0 to 5			
Diethylene Glycol Ethyl Ether	111-90-0	0 to 5			
Dipropylene Glycol Methyl Ether	34590-94-8	0 to 5			

SECTION 3-PHYSICAL DATA

Boiling Point (°F): 212 F.
Vapor Pressure: 20mm Hg @ 68 F.
% Volatile: 70+
Solubility in Water: Complete
Physical Description: Thin milky liquid with characteristic odor.

Specific Gravity: 1.039
Vapor Density (Air=1): >1
pH: 8.0-9.0
Evaporation Rate (Water=1): <1

SECTION 4-FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): None
Upper Explosion Limit: N/A
Lower Explosion Limit: N/A
Extinguishing Media: N/A
Special Firefighting Procedures: Non Flammable
Unusual Fire and Explosion Hazards: N/A

SECTION 5-REACTIVITY DATA

Stability: Stable
Hazards Decomposition Products: Will not occur.

Hazardous Polymerization: None
Incompatibility (Materials to Avoid): None

SECTION 6-STORAGE AND HANDLING INFORMATION

Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only. Avoid contact with eyes, skin and clothing. Avoid breathing of vapors. Use in well-ventilated area.

SECTION 7-HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:
Skin: Prolonged or repeated contact may cause dermatitis.
Eyes: Eye irritant. May cause redness or swelling.
Inhalation: Vapors may cause headache, dizziness, nausea.
Ingestion: May be irritating to the mouth, throat, and gastrointestinal system.
 Vomiting and diarrhea expected with large doses.

First Aid Procedures:

Skin: Flush with water. Seek medical attention if irritation persists.
Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention.
Inhalation: Remove victim to fresh air and monitor.
Ingestion: Dilute with 2 glasses of water. Seek medical attention if symptoms persist.

SECTION 8-SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use in well-ventilated area.
Ventilation Requirements: Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit.
Protective Gloves: Chemical resistant rubber or neoprene.
Eye Protection: Safety glasses or chemical splash goggles
Other Protective Equipment: Protective footwear (rubber boots) should be worn when using product on floor.

SECTION 9-SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.
Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. Consult local authorities for disposal in public sewer. Do not dispose of into storm drain, stream, river or to ground. Rinse container thoroughly before discarding in trash.

SECTION 10-REGULATORY INFORMATION

SARA Title III - Section 311/312 -Hazard Categories:
 No - Fire Hazard
 No - Sudden Release of Pressure Hazard
 No - Reactivity Hazard
 Yes - Immediate (acute) Health Hazard
 No - Delayed (chronic) Health Hazard

Shipping Information:
 FOR CONTAINERS > 1 Gallon : Liquid Floor Wax
 FOR 1 GALLON CONTAINERS : Liquid Floor Wax
 FOR CONTAINERS < 1 GALLON : Liquid Floor Wax

HMS Hazardous Materials Identification System

Health	1
Flammability	0
Reactivity	0
Personal Protection	A

FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: ER# 1-888-779-1339

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS#	Chemical Name	Percent by Weight
	None	

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.

CAS#	Chemical Name	Percent by Weight
	None	

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product