

PRO SERIES

BASELINE

ACRYLIC FLOOR SEALER

SELLADOR DE ACRÍLICO DEL PISO



Technical Data

Areas of Use

- Health care
- Schools
- Retail Buildings
- Offices
- Any facility using a low maintenance program

Specifications

SSS Item Numbers	48086
Available Sizes	2.5G
Type	Modified acrylic
Physical State	Liquid
Non-volatile solids:	18.0±0.5%
Color	Milky white
Fragrance	Mild
pH	8.6 +/- 0.5
Dry/Recoat Time	30 minutes
Slip Resistance	0.5 min. by ASTM D2047
Leveling	Excellent
Sediment	0.1% by volume, max.
Removability	With conventional strippers
Detergent Resistance	Excellent
Stain Resistance	Good
Scuff Resistance	Excellent
Chemical Resistance	Good
VOC Content	0.31 lbs./gal.
Viscosity	Water thin
Storage/Stability	2 years
Freeze/Thaw Stability	Keep from freezing
Weight Per Gallon	8.56 lbs./gal.
Coverage	1000-1500 sq. ft./gal. 1500-2000 sq. ft./gal.

HMIS Hazardous Materials I.D. System

Health.....	1
Flammability.....	0
Reactivity.....	0
Personal Protection.....	A

What the Pros Know

The use of a microfiber applicator will result in exceptional flow and leveling, and will help keep the finish off of the baseboards.

Description

An all-acrylic floor sealer formulated to provide a hard, durable undercoat for use prior to the application of any floor polish. Never yellows and will continue to protect your floor after all floor finish or wax has worn off.

Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



Make sure floor has been thoroughly stripped and rinsed and allowed to dry. For porous or well-worn floors, apply 2 coats of sealer followed by 2 or more coats of finish depending on the gloss desired.

On new floor or floors in good condition, one coat of sealer should suffice.

Never Yellows

Continues to Protect When Finish is Worn Off

Excellent Leveling



MATERIAL SAFETY DATA SHEET

Prepared by: Regulatory Affairs Dept.

(Prepared According to 29 CFR 1910.1200)

N/A=Not Applicable
Effective Date: 5/10 Revision: n/a

SECTION 1-PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Product Name: Baseline
Generic Name: Acrylic Floor Sealer
Chemical Family: Acrylic Wax Blend
Formula: Proprietary
Triple S Product Number: 48086

Manufactured For: Triple S
Address: 2 Executive Park Drive Billerica, MA 01862
Phone #: 800-323-2251

SECTION 2-INGREDIENT INFORMATION

CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Water	7732-18-5	to 100			
Acrylic Copolymer Dispersion	63744-68-3	35 to 40			
Resin Solution	65405-63-2	5 to 10			
Polyethylene Wax	68441-17-8	5 to 10			
Tributoxy Ethyl Phosphate	78-51-3	0 to 5			
Diethylene Glycol Monomethyl Ether	111-77-3	0 to 5			

SECTION 3-PHYSICAL DATA

Boiling Point (°F): 212 F.
Vapor Pressure: 20mm Hg @ 68 F.
% Volatile: 82 +
Solubility in Water: Complete
Physical Description: Thin milky liquid with characteristic odor.

Specific Gravity: 1.028
Vapor Density (Air=1): >1
pH: 8.6 +/- 0.5
Evaporation Rate (Water=1): <1

SECTION 4-FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/A
Upper Explosion Limit: N/A
Lower Explosion Limit: N/A
Extinguishing Media: N/A
Special Firefighting Procedures: Non Flammable
Unusual Fire and Explosion Hazards: N/A

SECTION 5-REACTIVITY DATA

Stability: Stable
Hazards Decomposition Products: Will not occur.

Hazardous Polymerization: None
Incompatibility (Materials to Avoid): None

SECTION 6-STORAGE AND HANDLING INFORMATION

Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only. Avoid contact with eyes, skin and clothing. Wear protective gloves, eyewear and footwear when applying. Avoid breathing of vapors. Use in well-ventilated area.

SECTION 7-HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:
Skin: Prolonged or repeated contact may cause dermatitis.
Eyes: Eye irritant. May cause redness or swelling.
Inhalation: Vapors may irritate nose, throat and lungs. May cause dizziness, headache, and nausea.
Ingestion: May be irritating to the mouth, throat, and gastrointestinal system. Vomiting and diarrhea expected with large doses.
First Aid Procedures:
Skin: Flush with water. Seek medical attention if irritation persists.
Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention.
Inhalation: Remove victim to fresh air and monitor.
Ingestion: Dilute with 2 glasses of water. Seek medical attention if symptoms persist.

SECTION 8-SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use in well-ventilated area.
Ventilation Requirements: Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit.
Protective Gloves: Chemical resistant rubber or neoprene.
Eye Protection
Other Protective Equipment: Eyewash should be nearby. Wear rubber boots and protective outerwear when using.

SECTION 9-SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.
Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. Consult local authorities for disposal in public sewer. Do not dispose of into storm drain, stream, river or to ground. Rinse container thoroughly before discarding in trash.

SECTION 10-REGULATORY INFORMATION

SARA Title III - Section 311/312 -Hazard Categories:
No - Fire Hazard
No - Sudden Release of Pressure Hazard
No - Reactivity Hazard
Yes - Immediate (acute) Health Hazard
No - Delayed (chronic) Health Hazard

Shipping Information:
FOR CONTAINERS > 1 Gallon : Liquid Floor Wax
FOR 1 GALLON CONTAINERS : Liquid Floor Wax
FOR CONTAINERS < 1 GALLON : Liquid Floor Wax

HMIS Hazardous Materials Identification System

Health	1
Flammability	0
Reactivity	0
Personal Protection	A

FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: ER# 1-888-779-1339

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS#	Chemical Name	Percent by Weight
	None	

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.

CAS#	Chemical Name	Percent by Weight
	None	

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product.