

PRO SERIES

RED ZONE

**HIGH POWERED
LOW ODOR FLOOR STRIPPER**
SEPARADOR DEL PISO

Technical Data

Areas of Use

- Vinyl Tile
- Terrazzo
- Ceramic Tile
- Flagstone

Specifications

SSS Item Number48110
Available Sizes1Qt
ColorLight Amber
FragranceMild odor
pH11.0 - 12.0
ViscosityWater thin
FoamLow
Phosphate ContentNone
SolubilityComplete with water
Flash Point200°F (TCC)
Storage/Stability2 years
Weight Per Gallon8.45 lbs./gal.
Freeze/Thaw StabilityKeep from freezing

HMIS Hazardous Materials I.D. System

Health3
Flammability1
Reactivity0
Personal ProtectionD

What the Pros Know

When stripping a floor, it is recommended to flood the floor using 1 gallon of diluted stripper for 100 square feet of flooring.

Description

An ultra concentrated (1:20) high-powered stripper that rapidly penetrates and strips off floor finish. A powerful solvent combined with amines, penetrates and removes multiple coats of burnished finish with minimum labor. Low odor formula is ideal for use in areas where odors are a concern. This high productivity floor stripper strips floor finishes completely on the one pass and requires no rinse. This unique formula provides the lowest end-use cost per gallon due to its ultra concentration.

DO NOT USE THIS PRODUCT ON WOOD FLOORS OR PAINTED SUFRACES.

Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



Sweep or dust mop the floor to remove any debris.

The desired concentration will depend on the build-up and age of the polish film. As a starting point, dilute with cold water or mildly warm water as follows:

1. Simply add a quart of product to a mop bucket. Fill the mop bucket with water up to 5 gallons.
2. The stripping solution may be applied with a mop or automatic scrubber. Allow to stand for 5 - 10 minutes. **DO NOT ALLOW TO DRY.** Scrub with a rotary floor machine or automatic scrubber equipped with stripping pads.
3. Pick-up the solution and old finish with a wet vacuum or clean mop.
4. Rinse thoroughly with clean cold water.
5. Allow floor to dry completely before applying any floor finish.

NOTE:

The product must be used only as directed due to its unique penetrating and liquifying ability. Do not use undiluted product. Do not dilute with hot water. To determine the optimum use-dilution, pretest on a small area. Wet floor may become extremely slippery. Be sure to keep pedestrian traffic away from floor until thoroughly dry. Work area should have adequate ventilation since prolonged exposure to high concentrations of vapors may be harmful to eyes, skin and respiratory tracts. As prolonged soaking in concentrated strippers may damage some asphalt tiles, a spot test is recommended before general use.



*Ultra
Concentrated-
One Quart Makes
5 Gallons*

Low Odor

*Low End Use
Cost*

