

FRONTLINE

SURFACE PROTECTOR



Technical Data

Areas of Use

- Institutional Facilities
- Architectural/Industrial Maintenance
- Building/Facility Maintenance
- Parking Garages
- General Contractors
- Painting Contractors
- Retail/Shopping Centers
- Property Maintenance
- Sound Barriers/Noise Walls
- Event Centers
- Stadiums/Arenas
- Service Contractors

Specifications

Available Sizes.....	4/1G, 1/5G
Physical State.....	Liquid
Color.....	Milky White
Fragrance.....	Very Mild Solvent Odor
pH.....	8
Shelf Life.....	12 Months
<u>HMIS Hazard Rating</u>	
Health.....	1
Flammability.....	0
Physical Hazard.....	0
Personal Protection.....	B

What the Pros Know

- Can be used on EIFS, cement plaster and stucco.
- Works on previously or newly painted surfaces.
- Great for sensitive surfaces – like murals and architectural structures.
- Performs on aggregate panels.

Description

- Clear, non-yellowing natural finish
- Designed for a variety of interior and exterior hard surfaces
- Versatile application methods
- No alteration or damage to the original surface
- Multiple coats can be applied quickly
- Immediate graffiti protection after application
- Fast and easy removal and re-application
- Biodegradable and easy water clean up
- Cost effective - saves time and money

FRONTLINE Surface Protector is a sacrificial graffiti resistant coating formulated with a blend of waxes and resins. FRONTLINE is designed to give optimum performance as a protective sacrificial coating over most interior and exterior hard surfaces. FRONTLINE provides a temporary barrier against graffiti damage caused by most spray paint and markers with easy removal by hot pressure washing or appropriate Triple S graffiti remover. Frontline can be applied to brick, concrete, masonry, stucco, wood painted surfaces, metal plastic and more.

Directions

Apply to dry surface with brush, roller, or airless sprayer; allowing 30 minutes between coats. Remove by hot pressure washing or recommended appropriate Triple S graffiti remover. Application rates are variable and increase with repeat coats. Three coats recommended on smooth surfaces and four coats on porous surfaces.

FIRST COAT COVERAGE RATES:
 Painted surfaces, metal, plastic.....300-500 sq. ft. /Gal.
 Concrete, brick, wood, stucco.....150-300 sq. ft. / Gal.
 Block, porous masonry.....75-150 sq. ft. / Gal.

Sacrificial Surface Protector

•

Easy to Apply & Quick Removal

•

Safe for Surface & Environment

